

## LCD Projector

HC5000


# *Controlling the projector using a personal computer*

This projector can be controlled by connecting a personal computer with RS-232C terminal.

### PC-controllable functions:

- Turning the power ON or OFF
- Changing input signals
- Inputting commands by pressing the buttons on the control panel and remote control
- Menu setting

### Connection



### Important:

- Make sure that your computer and projector are turned off before connection.
- Boot up the computer first, and then plug the power cord of the projector.  
(If you do not follow this instruction, the Com port may not function.)
- Adapters may be necessary depending on the PC connected to this projector. Contact your dealer for details.

### 1) Interface

PROTOCOL	RS-232C
BAUD RATE	9600 [bps]
DATA LENGTH	8 [bits]
PARITY BIT	NONE
STOP BIT	1 [bit]
FLOW CONTROL	NONE

This projector uses RXD, TXD and GND lines for RS-232C control.  
For RS-232C cable, the reverse type cable should be used.

### 2) Control command diagram

The command consists of the address code, function code, data code, and end code. The length of the command varies among the functions.

	Address code	Function code	Data code	End code
HEX	30h 30h	Function	Data	0Dh
ASCII	'0' '0'	Function	Data	↵

[Address code] 30h 30h (In ASCII code, '0' '0') fixed.

[Function code] A code of each fixed control move.

[Data code] A code of each fixed control data (number) and not always indicated.

[End code] 0Dh (In ASCII code, '↵') fixed.

### 3) Control sequence

- (1) Send the command from the personal computer to the projector.
  - (2) The projector will send a return command after it receives an end code. If the command is not received correctly, the projector will not send the return command.
  - (3) The personal computer checks the command and confirms if the sent command has been executed or not.
  - (4) This projector sends various codes other than the return code. When having a control sequence by RS-232C, reject other codes from the personal computer.
- During signal switching, the command may not take effect even when the projector sends the return command. After signal switching completes, wait for the mode indication to disappear before sending the next command.
  - When sending commands successively, wait to receive the return command of the current command before sending a next command.
  - Keep intervals of at least 400 ms between receipt of a return command and sending of a next command.
  - Any commands will not be executed for 10 seconds after the power is turned on.

[Example] When turning the power ON. (Figures and symbols enclosed in quotation marks are ASCII codes.):

Sending commands from the PC, etc.	Status code from the projector	Description
30 30 21 0D '0' '0' '!' '␣'		Command for POWER ON
	30 30 21 0D '0' '0' '!' '␣'	Command receipt confirmation (Command echo back)

### 4) Operation commands (Not executable in stand-by mode. When the commands for input select are sent while the splash screen is being displayed, the splash screen is only canceled.)

The operation commands are used for the basic operation setting of this projector. They may not be executed while the signals are changed. The operation commands have no data codes.

Operation	ASCII	HEX	Note
POWER ON	!	21h	This command is invalid for 1 minute after the power is turned off.
POWER OFF	"	22h	This command is invalid for 1 minute after the power is turned on.
INPUT COMPUTER	_r1	5Fh 72h 31h	This command will not be executed in Stand-by mode.
INPUT COMPONENT	_c1	5Fh 63h 31h	This command will not be executed in Stand-by mode.
INPUT HDMI	_d1	5Fh 64h 31h	This command will not be executed in Stand-by mode.
INPUT DVI	_d2	5Fh 64h 32h	This command will not be executed in Stand-by mode.
INPUT VIDEO	_v1	5Fh 76h 31h	This command will not be executed in Stand-by mode.
INPUT S-VIDEO	_v2	5Fh 76h 32h	This command will not be executed in Stand-by mode.

[Example] When setting the input signal to COMPUTER. (Figures and symbols enclosed in quotation marks are ASCII codes.):

Sending commands from the PC, etc.	Status code from the projector	Description
30 30 5F 72 31 0D '0' '0' '_' 'r' '1' '␣'		Command for setting the input signal to COMPUTER
	30 30 5F 72 31 0D '0' '0' '_' 'r' '1' '␣'	Command receipt confirmation (Command echo back)

### 5) Remote commands (Not executable in stand-by mode. When the remote commands are sent while the splash screen is being displayed, the splash screen is only canceled.)

Some remote control operations can be achieved by the remote command codes. The remote commands have no data codes.

Button's name on remote	ASCII	HEX	Button's name on remote	ASCII	HEX
▲	r53	72h 35h 33h	CONTRAST	rd0	72h 64h 30h
▼	r2b	72h 32h 62h	BRIGHTNESS	rd1	72h 64h 31h
◀	r4f	72h 34h 66h	COLOR TEMP.	rd4	72h 64h 34h
▶	r59	72h 35h 39h	GAMMA	rd5	72h 64h 35h
MENU	r54	72h 35h 34h	SHARPNESS	rd6	72h 64h 36h
ENTER	r10	72h 31h 30h	AUTO IRIS	r55	72h 35h 35h
AUTO POSITION	r09	72h 30h 39h	COLOR	rd2	72h 64h 32h
ASPECT	re2	72h 65h 32h	ZOOM/FOCUS	r0f	72h 30h 66h
AV MEMORY 1	re4	72h 65h 34h	LENS SHIFT	r47	72h 34h 37h
AV MEMORY 2	re5	72h 65h 35h	NOISE REDUCTION	rf7	72h 66h 37h
AV MEMORY 3	re6	72h 65h 36h			

[Example] When displaying the MENU selection bar. (Figures and symbols enclosed in quotation marks are ASCII codes.):

Sending commands from the PC, etc.	Status code from the projector	Description
30 30 72 35 34 0D '0' '0' 'r' '5' '4' '↵'		Command operating the same as the MENU button
	30 30 72 35 34 0D '0' '0' 'r' '5' '4' '↵'	Command receipt confirmation (Command echo back)

## 6) Password lock commands

The password lock commands control the password lock. The password lock enabling or disabling command is sent with a 4 to 8-digit password comprised of any figures 1 to 4 added to the end of the data code. When the password lock is enabled or disabled successfully, the projector sends a return command comprising the data code, password, and “1” at the end. When enabling or disabling the password lock fails, it sends a return command with “0” at the end. There is no reconfirmation of the password. The password input command is for enabling projection of image when password lock has been set to DISPLAY INPUT. The password input command is sent with a 4 to 8-digit password comprised of any figures 1 to 4 at the end.

ITEM	ASCII	HEX	VALUE
Password lock enabling/disabling	PSLOCK	50h 53h 4Ch 4Fh 43h 4Bh	0**** (Disabling), 1**** (DISPLAY INPUT), 2**** (MENU ACCESS)
Password input	PASS	50h 41h 53h 53h	****

\*\*\*\* is a 4 to 8-digit password comprised of any figures 1 to 4.

[Example] When enabling the password lock of DISPLAY INPUT (in the case that the password is 123412). (Figures and symbols enclosed in quotation marks are ASCII codes.):

Sending commands from the PC, etc.	Status code from the projector	Description
30 30 50 53 4C 4F 43 4B 31 31 32 33 34 31 32 0D '0' '0' 'P' 'S' 'L' 'O' 'C' 'K' '1' '1' '2' '3' '4' '1' '2' '↵'		Command for enabling the password lock of DISPLAY INPUT
	30 30 50 53 4C 4F 43 4B 31 31 32 33 34 31 32 31 0D '0' '0' 'P' 'S' 'L' 'O' 'C' 'K' '1' '1' '2' '3' '4' '1' '2' '1' '↵'	Response informing that the projector succeeded in enabling the password lock of DISPLAY INPUT

## 7) Reading command diagram

The projectors operating status, such as POWER-ON/OFF and the currently selected input terminal, etc. can be monitored.

	ASCII		HEX	
	Function	Data (Receive)	Function	Data (Receive)
POWER ON	vP	1	76h 50h	31h
POWER OFF	vP	0	76h 50h	30h
INPUT COMPUTER	vI	r1	76h 49h	72h 31h
INPUT COMPONENT	vI	c1	76h 49h	63h 31h
INPUT HDMI	vI	d1	76h 49h	64h 31h
INPUT DVI	vI	d2	76h 49h	64h 32h
INPUT VIDEO	vI	v1	76h 49h	76h 31h
INPUT S-VIDEO	vI	v2	76h 49h	76h 32h
POWER ON/OFF IMPOSSIBLE	vPK	0	76h 50h 4Bh	30h
POWER ON/OFF POSSIBLE	vPK	1	76h 50h 4Bh	31h
NO SIGNAL SUPPLIED	vSM	0	76h 53h 4Dh	30h
SIGNAL SUPPLIED	vSM	1	76h 53h 4Dh	31h
LAMP OPERATING TIME (on the LOW mode basis)	vLE	hhhhmm	76h 4Ch 45h	hhhh mm

The PC sends the command without attaching the data code to it. On the other hand, the projector attaches to the received command its current operating status as the data code and send it back to the PC.

[Example] When checking the currently selected input terminal (when the INPUT VIDEO is being selected). (Figures and symbols enclosed in quotation marks are ASCII codes.):

Sending commands from the PC, etc.	Status code from the projector	Description
30 30 76 49 0D '0' '0' 'v' 'I' '↵'		Command for checking the input terminal
	30 30 76 49 76 31 0D '0' '0' 'v' 'I' 'v' '1' '↵'	Check result (VIDEO)

8) Menu setting commands (Not executable in stand-by mode. Possible only to read during muting.)

The menu setting commands are used for the menu setting of this projector. If the personal computer sends the command without attaching the data code, the projector attaches to the received command its current setting value as the data code and send it back to the PC.

ITEM	ASCII	HEX	VALUE
GAMMA MODE	GS	47h 53h	<b>0</b> (SPORTS), <b>1</b> (VIDEO), <b>2</b> (CINEMA), <b>3</b> (USER1), <b>4</b> (USER2), <b>5</b> (AUTO)
GAMMA MODE-USER1	GSU1	47h 53h 55h 31h	<b>R, G, B, +0</b> (SPORTS), <b>+1</b> (VIDEO), <b>+2</b> (CINEMA), <b>±10 ±10 ±10</b> (HIGH, MID, LOW)
GAMMA MODE-USER2	GSU2	47h 53h 55h 32h	<b>R, G, B, +0</b> (SPORTS), <b>+1</b> (VIDEO), <b>+2</b> (CINEMA), <b>±10 ±10 ±10</b> (HIGH, MID, LOW)
CONTRAST	PP	50h 50h	<b>±30</b>
BRIGHTNESS	QQ	51h 51h	<b>±30</b>
COLOR TEMP.	A	41h	<b>1</b> (COOL), <b>2</b> (MEDIUM), <b>3</b> (WARM), <b>4</b> (USER), <b>5</b> (HIGH BRIGHTNESS)
COLOR TEMP.-USER (CONTRAST)	P	50h	<b>±30 ±30 ±30</b> (R, G, B)
COLOR TEMP.-USER (BRIGHTNESS)	Q	51h	<b>±30 ±30 ±30</b> (R, G, B)
COLOR	T	54h	<b>±10</b>
TINT	S	53h	<b>±10</b>
SHARPNESS	R	52h	<b>±10</b>
SCREEN SIZE	SCR	53h 43h 52h	<b>0</b> (16:9), <b>1</b> (CINEMA SCOPE 2.35:1)
VERTICAL LOCATION	IMP	49h 4Dh 50h	<b>±26</b>
AUTO IRIS	IRIS	49h 52h 49h 53h	<b>0</b> (OPEN), <b>1</b> (AUTO IRIS 1), <b>2</b> (AUTO IRIS 2), <b>3</b> (AUTO IRIS 3)
TRNR	TRNR		<b>00 - 15</b>
MNR	MNR		<b>00 - 15</b>
BAR	BAR		<b>0</b> (OFF), <b>1</b> (ON)
CTI	CTI		<b>0 - 5</b>
INPUT LEVEL	IPL		<b>±5</b>
LAMP MODE	LM	4Ch 4Dh	<b>0</b> (STANDARD), <b>1</b> (LOW)
AUTO POWER ON	APON	41h 50h 4Fh 4Eh	<b>0</b> (OFF), <b>1</b> (ON)
AUTO POWER OFF	APOF	41h 50h 4Fh 46h	<b>00</b> (OFF), <b>05, 10, 15, 30, 60</b>
SPLASH SCREEN	SS	53h 53h	<b>0</b> (OFF), <b>1</b> (ON)
BACK COLOR	BB	42h 42h	<b>0</b> (BLACK), <b>1</b> (BLUE)
IMAGE REVERSE	IR	49h 52h	<b>0</b> (OFF), <b>1</b> (MIRROR), <b>2</b> (INVERT), <b>3</b> (MIRROR INVERT)
TRIGGER OUT	SCT	53h 43h 54h	<b>0</b> (OFF), <b>1</b> (ON)
TEST PATTERN	TP	54h 50h	<b>0</b> (OFF), <b>1</b> (CROSS HATCH)
FOCUS/ZOOM LOCK	FZL		<b>0</b> (OFF), <b>1</b> (ON)
LENS SHIFT LOCK	LSL	4Ch 53h 4Ch	<b>0</b> (OFF), <b>1</b> (ON)
LENS SHIFT RESET	LSRST	4Ch 53h 52h 53h 54h	
ASPECT	SC	53h 43h	<b>0</b> (AUTO), <b>1</b> (4:3), <b>2</b> (16:9), <b>3</b> (ZOOM1), <b>4</b> (ZOOM2), <b>5</b> (STRETCH)
PASSWORD FUNCTION	PSLOCK	50h 53h 4Ch 4Fh 43h 4Bh	0**** (UNLOCK), 1**** (DISPLAY INPUT), 2**** (MENU ACCESS) **** is a 4 to 8-digit password comprised of any figures 1 to 4.
MENU POSITION	MP	4Dh 50h	<b>0</b> (Upper left), <b>1</b> (Lower right)
CINEMA MODE	CINE	43h 49h 4Eh 45h	<b>0</b> (OFF), <b>1</b> (AUTO)
VIDEO SIGNAL (VIDEO only)	VS	56h 53h	<b>0</b> (AUTO), <b>1</b> (NTSC), <b>2</b> (PAL), <b>3</b> (SECAM), <b>4</b> (4.43NTSC), <b>5</b> (PAL-M), <b>6</b> (PAL-N), <b>7</b> (PAL-60)
SET UP	STU	53h 54h 55h	<b>0</b> (AUTO), <b>1</b> (OFF), <b>2</b> (3.75%), <b>3</b> (7.5%)
SCART INPUT	SRT	53h 52h 54h	<b>0</b> (OFF), <b>1</b> (ON)
LANGUAGE	LG	4Dh 47h	<b>0</b> (日本語), <b>1</b> (English), <b>2</b> (Español), <b>3</b> (Deutsch), <b>4</b> (Français), <b>5</b> (Italiano), <b>6</b> (中文), <b>7</b> (한국어), <b>8</b> (РУССКИЙ), <b>9</b> (Português)
RESET ALL	RSTALL	52h 53h 54h 41h 4Ch 4Ch	
HORIZ.POSITION	HP	48h 50h	<b>+</b> : increment, <b>-</b> : decrement *1
VERT.POSITION	VP	56h 50h	<b>+</b> : increment, <b>-</b> : decrement *1
FINE SYNC.	FN	46h 4Eh	<b>00 - 31</b>
TRACKING	TRK	54h 52h 4Bh	<b>+</b> : increment, <b>-</b> : decrement *1
COMPUTER INPUT	CIN	43h 49h 4Eh	<b>0</b> (RGB), <b>1</b> (YCbCr/YPbPr), <b>2</b> (AUTO)
OVER SCAN	VOS	56h 4Fh 53h	<b>00</b> (90%) - <b>10</b> (100%)
HOLD	HLD	48h 4Ch 44h	<b>0</b> (OFF), <b>1</b> (ON)
HOLD BEGIN	HLB	48h 4Ch 42h	<b>00 - 99</b>
HOLD END	HLE	48h 4Ch 45h	<b>00 - 99</b>

ITEM	ASCII	HEX	VALUE
CLAMP POSITION	CLP	43h 4Ch 50h	<b>001 - 255</b>
CLAMP WIDTH	CLW	43h 4Ch 57h	<b>01 - 63</b>
VERT.SYNC.	VSC	56h 53h 43h	<b>0 (OFF), 1 (AUTO)</b>
LPF	LPF	4Ch 50h 46h	<b>0 (OFF), 1 (ON)</b>
SHUTTER(U)	SHU	53h 48h 55h	<b>00 - 32</b>
SHUTTER(L)	SHL	53h 48h 4Ch	<b>00 - 32</b>
SHUTTER(LS)	SHLS	53h 48h 4Ch 53h	<b>00 - 95</b>
SHUTTER(RS)	SHRS	53h 48h 52h 53h	<b>00 - 95</b>

\*1) Setting range differs depending on the input signals.

- Some commands are not executed depending on the input signal. The operational restrictions same as those on the menu setting are applied. Refer to “Menu operation” in the User Manual for more details.

### How to set the value

Use the ASCII or HEX code as shown below to set the value.

ASCII	'+'	'-'	'0'	'1'	'2'	'3'	'4'	'5'	'6'	'7'	'8'	'9'
HEX	2Bh	2Dh	30h	31h	32h	33h	34h	35h	36h	37h	38h	39h

[Example 1] When setting the AUTO POWER ON to ON. (Figures and symbols enclosed in quotation marks are ASCII codes.):

Sending commands from the PC, etc.	Status code from the projector	Description
30 30 41 50 4F 4E 31 0D '0' '0' 'A' 'P' 'O' 'N' '1' '␣'		Command for setting the AUTO POWER ON to ON
	30 30 41 50 4F 4E 31 0D '0' '0' 'A' 'P' 'O' 'N' '1' '␣'	Command receipt confirmation (Command echo back)

[Example 2] When setting the CONTRAST R of the COLOR TEMP.-USER to +10, the CONTRAST G to 0, and the CONTRAST B to -5. (Figures and symbols enclosed in quotation marks are ASCII codes.):

Sending commands from the PC, etc.	Status code from the projector	Description
30 30 50 2B 31 30 2B 30 30 2D 30 35 0D '0' '0' 'P' '+' '1' '0' '+' '0' '0' '-' '0' '5' '␣'		Command for setting the picture control
	30 30 50 2B 31 30 2B 30 30 2D 30 35 0D '0' '0' 'P' '+' '1' '0' '+' '0' '0' '-' '0' '5' '␣'	Command receipt confirmation (Command echo back)

[Example 3] When checking the TINT setting (when the TINT is set to +10). (Figures and symbols enclosed in quotation marks are ASCII codes.):

Sending commands from the PC, etc.	Status code from the projector	Description
30 30 53 0D '0' '0' 'S' '␣'		Command for checking the TINT setting
	30 30 53 2B 31 30 0D '0' '0' 'S' '+' '1' '0' '␣'	Check result (+10)

- To set TINT at 0, enter +00. (-00 is invalid.)

[Example 4] When setting the REFERENCE of GAMMA MODE-USER1 to CINEMA (+2), ADJUST MODE to RED (R), HIGH to -2, MID to +3 and LOW to 0. (Figures and symbols enclosed in quotation marks are ASCII codes.):

- \* There is no command for selecting ALL for ADJUST MODE. Even when you want to set all the three colors to the same value, send a command for each of R, G, and B respectively.

Sending commands from the PC, etc.	Status code from the projector	Description
30 30 47 53 55 31 52 2B 32 2D 30 32 2B 30 33 2B 30 30 0D '0' '0' 'G' 'S' 'U' '1' 'R' '+' '2' '-' '0' '2' '+' '0' '3' '+' '0' '0' '␣'		Command for setting GAMMA MODE-USER1
	30 30 47 53 55 31 52 2B 32 2D 30 32 2B 30 33 2B 30 30 0D '0' '0' 'G' 'S' 'U' '1' 'R' '+' '2' '-' '0' '2' '+' '0' '3' '+' '0' '0' '␣'	Command receipt confirmation (Command echo back)